

Locking or Unlocking by RFID

When you swipe the authorized RFID card, the K211 Series can be locked or unlocked.

78 days of battery life

Internal 14000 mAh battery, support interactive working mode by LoRa.

## APPLICATION



GNSS SMART LOC





## **SPECIFICATIONS**

| ITEM                                   | SPECIFICATIONS  |
|--|---|
| Dimension                              | 112 mm x 195 mm x 37 mm   |
| Lock rope length                       | 300 mm (The length can be customized as needed.)  |
| Weight                                 | 800g  |
| Power supply                           | DC 9–14 V; 2 A  |
| Material                               | The outer case of the device adopts PC materials  |
| Backup battery                         | 14000 mAh/3.7 V   |
| Power consumption                      | Current in standby (sleep) mode: 9 mA<br>Current in normal working mode: 95 mA  |
| Charging time                          | 7.5–8 hours   |
| Operating temperature                  | -20°C to 55°C   |
| Operating humidity                     | 5%-95 %   |
| Working hour                           | Power-saving mode: 78 days<br>Normal working mode: 150 hours  |
| Charging                               | Magnetic charging (DC 9 V; 2 A; fast charging)  |
| Water resistance rating                | IP67  |
| GPS antenna                            | Built-in GPS antenna  |
| GPS sensitivity                        | -161 dB   |
| Positioning accuracy                   | 2.5 meters  |
| LoRa communication distance (optional) | At most 20 meters (obtained from actual tests in trucks' containers)  |
| LoRa working frequency (optional)      | 137–1020 MHz (433 MHz by default)   |
| LoRa antenna (optional)                | Built-in spring antenna   |
| RFID module frequency                  | 125 KHz   |
| Memory                                 | 64 MB   |
| SIM card installation                  | Flip the card slot cover to install Micro SIM cards; dual SIM cards   |
| Frequency band                         | K211L-ER:<br>LTE-FDD: B1/B3/5/B7/B8/B20/B28<br>GSM: 850/900/1800/1900 MHz   |
|  | K211L-AUR:<br>LTE-FDD: B2/B3/B4/B5/B7/B8/B28/B66<br>GSM: 850/900/1800/1900  |
|  | K211E:<br>LTE Cat M1/NB2: B1/B2/B3/B4/B5/B8/B12/B13/B14/B18/B19/B20/B25/<br>B26/B27/B28/B66/B71/B85<br>GSM: 850/900/1800/1900 MHz |



GNSS smart lock with the battery Lock rope (30 cm) RFID card Power adapter(9V) Magnetic USB charging cable USB cable (optional) CD download card







+86(755)83462818



www.meitrack.com



info@meitrack.com

