

4G Vehicle GNSS Tracker



Cost-effective

Lower price and more diversified functions for your choice.

Two-way Communication

External speaker and microphone, two-way communication can be realized.

Multifunctional

Support camera, fuel/temperature sensor, LED display, RFID/iButton, speaker, microphone and etc.

Driving Behavior Analysis

Detect driver behaviors, such as the driver fatigue, idling, harsh acceleration/braking, harsh cornering, collision, etc.

APPLICATION





School bus



Sanitation vehicle

Pranece Pranece

Ambulance

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	105 mm x 65 mm x 26 mm
Weight	190g
Power supply	DC 11–36 V/1.5 A
Backup battery	400 mAh/3.7 V
Power consumption	Standby mode: 5mA Normal mode: 65mA
Operating temperature	-20°C to 55°C (normal-temperature battery) -5°C to 75°C (high-temperature battery)
Operating humidity	5% to 95%
Working hour	47 hours in power-saving mode, 4.7 hours in normal mode
LED indicator	Green indicator showing the GSM signal Blue indicator showing the GPS signal
Button/Switch	1 SOS button (for sending SMSs or dialing) 1 power button
Memory	8 MB buffer
Sensor	3-axis accelerometer (used to wake the device up by vibration and detect towing alerts)
Frequency band	T333L: LTE-FDD: B1/B3/B5/B7/B8/B20/B28 LTE-TDD: B38/B40/B41 GSM: B2/B3/B5/B8
GPS sensitivity	-161 dB
Positioning accuracy	2.5m
I/O port	3 digital inputs (2 negative inputs and 1 positive input) 2 analog detection inputs 2 outputs 1 RS232 port 1 USB port 1-Wire® iButton 1-Wire® temperature sensor



ACCESSORIES

T333L with a built-in battery I/O cable + SOS button External 4G antenna External GPS antenna CD download card





+86(755)83462818



www.meitrack.com



info@meitrack.com

5/F, International Internet Finance Pioneer Park, No. 1, Taohua Rd., Futian Free Trade Zone, Shenzhen, China. 518038